

321907

**HAND HELD[®]
PRODUCTS**
a WelchAlllyn[®] affiliate

12345612345



IMAGETEAM™ 4710ESD

Hand Held or Fixed Mount 2D Image Readers for ESD-Sensitive and Clean Room Applications

The Hand Held Products IMAGETEAM™ (IT) 4710ESD 2D Image Readers are high performance readers of high density linear (1D), stacked (PDF417), and matrix (2D) codes, that have been designed specifically for the stringent requirements found in clean room assembly of sensitive electronic components. With a clean room rating of 100, ESD-resistant labeling, low particulation and contamination plastics, and ESD-resistant cables, the IT4710ESD readers are the most suitable hand held 2D image reader for ESD-sensitive and clean room environments today. Together with our IT3800ESD Hand Held Linear Imager, Hand Held Products offers the most complete line of ESD-resistant readers.

Internal components of the IT4710ESD 2D Image Reader are isolated from the conductive path formed by the case, output connector shield, and special shielded cable with drain wire. The 2D Image Reader is rated for discharges up to 15kV without damage. All materials are tested using the methods described in *ASTM D257, Standard Test Methods for Conductance of Insulating Materials*. The surface resistivity is rated at less than 10E5 ohms/square. Triboelectric residual charge measured with a no-contact electrostatic field meter is less than 5 volts on any surface.

The IT4710ESD 2D Image Reader provides omni-directional and auto-discrimination decoding for symbologies, such as Data Matrix, PDF417, QR, Aztec, Code 39, Code 128, Interleaved 2 of 5, Codabar, UPC, and EAN, as well as RSS-14, composite codes, postal codes, and MaxiCode. Additional symbologies will be added as required.

Two focal point models are available: the IT4710E-HD (2 inch (5.1 cm) focal point) which is ideal for reading matrix (2D) symbols that have cell sizes less than 10 mil (.010 in.), and the IT4710E-HD10 (3 inch (7.6 cm) focal point) for reading matrix (2D) symbols with cell sizes greater than 10 mil (.010 in.). Both are excellent readers of high density linear (1D) symbols.

Features & Benefits

Supports All Popular 2D Symbologies

IT4710ESD supports all popular matrix and stacked linear symbologies: MaxiCode, Data Matrix, QR, and PDF417. Additional symbologies will be added as emerging codes are approved by AIM.

Clean Room Ready

Cleaned and triple-bagged for class 100 environments.

ESD Labels

Labels are located either behind the optically coated, grounded, conductive reader window inside the cable well, or are manufactured from conductive material and attached with conductive adhesive.

Low Particulation and Contamination

The housing material is slough-resistant and provides excellent electrostatic and grounding with low particulation. All labels on the outside of the reader are located far from the front of the reader.

ESD-Resistant Cables

Stainless steel, grounded cables, which eliminate one more source of electrostatic build up, are available for both true RS-232 and wedge interfaces.

Omni-Directional Scanning

The video technology basis for the IT4710ESD means it can offer omni-directional scanning, even on linear codes, greatly simplifying operator training and increasing productivity.

Auto-discriminates Between Supported Symbologies and Fonts

Reads all major linear, stacked linear, and matrix bar codes, as well as machine readable fonts used in Optical Character Recognition (OCR).

Performance

4710E-HD Focal Point: 2 inches (5.1 cm) from nose
4710E-HD10 Focal Point: 3 inches (7.6 cm) from nose

HD Working Range: (typical)	6 pt OCR 20 cpi	6.6 mil QR (.017 cm)	6.6 mil Data Matrix (.017 cm)	4 mil Linear (.01 cm)
Near	2 in. (5.1 cm)	1.7 in. (4.3 cm)	1.7 in. (4.3 cm)	1.6 in. (4.6 cm)
Far	3.5 in. (8.9 cm)	2.45 in. (6.2 cm)	2.45 in. (6.2 cm)	2.7 in. (6.9 cm)

HD10 Working Range: (typical)	10 mil QR (.025 cm)	10 mil Data Matrix (.025 cm)	5 mil Linear (.013 cm)
Near	2.0 in. (5.1 cm)	2.2 in. (5.6 cm)	2.75 in. (7.0 cm)
Far	4.0 in. (10.2 cm)	3.8 in. (9.6 cm)	3.75 in. (9.5 cm)

Rotational Sensitivity: 360°
Viewing Angle: ±45°
Ambient Light: Total darkness to 100,000 lux (full sunlight)
Aiming: 660nm LEDs provide bright aiming line

Symbologies

2 Dimensional: MaxiCode, PDF417, MicroPDF417, Aztec, Aztec Mesa, Data Matrix, QR Code, Code 49, UCC Composite, Snowflake*, Vericode*, Dataglyphs*

Linear: Code 39, Code 128, Codabar, UPC, EAN, I 2 of 5, RSS-14, BC 412*, Code 93, Codablock
 * available to licensed users only

Postal: Postnet (US), BPO4 State, Canadian 4 State, Japanese Post, KIX (Dutch Post), Planet Code

OCR Fonts: OCR-A, OCR-B

Interfaces: RS232, Wedge, and HHLC (Code 128 Emulation)

Programable

Options: Baud, Parity, Data Formatting, Code Options

Mechanical/Electrical**Dimensions**

Length: 4.85 in. (12.3 cm)
Height: 1.85 in. (4.7 cm)
Width: 2.50 in. (6.35 cm)
Weight w/o cord: 6.5 oz. (182 g) or less
Power Requirements: 4 to 9 volts
Current Draw: Low Power Mode - average @ 5 VDC-40mA
 Medium Power Mode - average @ 5 VDC-125mA
 High Power Mode - average @ 5 VDC-175mA
Standby Current: < 200µA @ 5V

Environmental**Temperature**

Operating: -0°C to 50°C

Storage: -40°C to +70°C

Humidity: 95% RH, non condensing at 50°C

Shock: 10 drops 5 ft. to concrete @ room temperature

ESD: Functional after 15KV discharge

Surface Resistivity: Less than 10E5 ohms/square inch as measured by ASTM D257, Standard Test Methods for Conductance of Insulating Materials

Triboelectric Residual

Charge: Less than 5 volts as measured by non-contact Electrostatic Field Meter

Agency: FCC Class A, CE



Complies with EMC 89/336/EEC and LVD 73/23/EEC

Worldwide Offices**Offices Serving North America**

Skaneateles Falls, NY
 Tel: (315) 685-8945
 Fax: (315) 685-3172

Charlotte, NC
 Tel: (704) 537-1444
 Fax: (704) 532-4191

Offices Serving Europe, Middle East, and Africa

Europe
 Tel: Int +31 (0) 40 24 24 486
 Fax: Int +31 (0) 40 24 25 672

United Kingdom
 Tel: Int +44 (0) 1 925 240055
 Fax: Int +44 (0) 1 925 631280

France
 Tel: Int +33 (0) 1 461 04111
 Fax: Int +33 (0) 1 461 04120

Germany

Tel: Int +49 (0) 7 477 151377
 Fax: Int +49 (0) 7 477 151378

Offices Serving Asia and the Pacific Rim

Hong Kong
 Tel: Int +852 2511 3050/2511 3132
 Fax: Int +852 2511 3557

Japan

Tel: Int +813 52127392
 Fax: Int +813 32617372

Offices Serving Latin America

Naples, Florida
 Tel: (941) 263-7600
 Fax: (941) 263-9689