



IMAGETEAM™ 4710LR/LX

Fixed Mount 2D Image Reader

The Hand Held Products IMAGETEAM™ (IT) 4710 Image Reader can be configured as either a hand held or fixed mount device that reads matrix, stacked linear, and conventional linear bar codes, as well as a single line of OCR-A and OCR-B fonts. Multi-line OCR applications can also be read. The IT4710 has the power to capture and download images to a PC for applications, such as signature capture, PC-based decoding, and image lift requirements.

The IT4710 Reader can be used in retail, packaging, transportation, printed circuit board manufacturing, electronic component manufacturing, and clinical/diagnostic applications that include test tube and reagent package labels.

The IT4710 can be configured for keyboard wedge, Non Decoded Output (Code 128 emulation), TTL, or True RS-232. The IT4710 connects to all popular PCs and portable data terminals. The Non Decoded Output mode can be used with external wedge decoders and portable terminals or other devices without 2D decoding capability.

The IT4710 features integrated processing for a one-piece scanning solution -- no additional boxes or electronics needed. The reader provides omni-directional and auto-discrimination decoding for symbologies, such as Maxi-Code, PDF417, QR, Data Matrix, Aztec code, RSS code, composite codes, postal codes, Code 39, Code 93, Interleaved 2 of 5, Codabar, Code 128, UPC, and EAN. Additional symbologies will be added based on market demand.

Because the IT4710 is a fixed focus device, four product models with different focal points are available. The IT4710LX, designed for reading wide codes at up to 15 inches on PDF, has a focal point of 7 inches from the nose. It is ideal for reading the 1D and 2D labels found in the transportation industry. The IT4710LR, designed for low and medium density codes, has a focal point of 5 inches from the nose. It is ideal for general 2D applications (postal, retail, and asset tracking). The high density (HD) models of the IT4710 are highlighted in a separate data sheet.

Features & Benefits

2D Image Reader

Hand held or fixed mount image reader for reading and decoding 2D symbologies, and capturing images.

Supports All Popular 2D Symbologies

Fixed mount IT4710 supports all popular matrix and stacked linear symbologies: MaxiCode, Aztec, Aztec Mesa, Data Matrix, PDF417, QR, and MicroPDF417.

Fixed Position Reader

Opens up new 2D bar code and image capture possibilities for fixed scanning applications.

Omni-Directional Scanning

CMOS-based video technology and image processing gives the IT4710 full omni-directional scanning, even on linear codes, greatly simplifying operator training and increasing productivity.

Aiming

The IT4710 has a bright, intuitive, aiming line.

Autodiscriminates Between Supported Symbologies and Fonts

Reads all major linear, stacked linear, and matrix bar codes as well as machine readable fonts used in Optical Character Recognition (OCR).

Performance

LX Focal Point: 7 inches from nose
LR Focal Point: 5 inches from nose

LX Working Range: (typical)	12 pt OCR-A 12 cpi	10 mil Linear (.025 cm)	13 mil UPC (.033 cm)	15 mil Data Matrix (.038 cm)	6.6 mil PDF (.017 cm)	10 mil PDF (.038 cm)
Near	1.6 in. (4.1 cm)	2.1 in. (5.3 cm)	2.3 in. (5.8 cm)	3.7 in. (9.4 cm)	4 in. (10.2 cm)	2.7 in. (6.9 cm)
Far	12.3 in. (31.2 cm)	9.5 in. (24.1 cm)	13 in. (33 cm)	5.9 in. (15 cm)	6.3 in. (16 cm)	9.8 in. (24.9 cm)

LR Working Range:	12 pt OCR 12 cpi	5 mil Linear (.013 cm)	13 mil Linear (.033 cm)	15 mil Data Matrix (.038 cm)	6.6 mil PDF (.017 cm)	10 mil PDF (.025 cm)
Near	1.9 in. (4.8 cm)	3 in. (7.6 cm)	1.9 in. (4.8 cm)	2 in. (5.1 cm)	2.7 in. (6.9 cm)	2.4 in. (6.1 cm)
Far	8.7 in. (22.1 cm)	4.3 in. (10.9 cm)	9.4 in. (23.9 cm)	5.8 in. (14.7 cm)	5.2 in. (13.2 cm)	7.7 in. (19.6 cm)

Rotational Sensitivity: 360°
Viewing Angle: ±45°
Ambient Light: Total darkness to 100,000 lux (full sunlight)
Aiming: 660nm LEDs provide bright aiming line

Symbologies

2 Dimensional: MaxiCode, PDF417, MicroPDF417, Aztec, Aztec Mesa, Data Matrix, QR Code, Code 49, UCC Composite, Snowflake*, Vericode*, Dataglyphs*
Linear: Code 39, Code 128, Codabar, UPC, EAN, I 2 of 5, RSS, BC 412*, Code 93, Codablock* available to licensed users only
Postal: Postnet (US), BPO4 State, Canadian 4 State, Japanese Post, KIX (Dutch Post), Planet Code
OCR Fonts: OCR-A, OCR-B
Interfaces: RS232, Wedge, and HHLC (Code 128 Emulation)
Programmable Options: Baud, Parity, Data Formatting, Code Options

Mechanical/Electrical

Dimensions

Length: 4.85 in. (12.3 cm)
Height: 1.85 in. (4.7 cm)
Width: 2.50 in. (6.4 cm)
Weight w/o cord: 5.5 oz. (156 g) or less
Power Requirements: 4 to 9 volts
Current Draw: Low Power Mode - average @ 5VDC-40mA
Medium Power Mode - average @ 5VDC - 125mA
High Power Mode - average @ 5VDC - 175mA
Standby Current: < 200µA @ 5V

Environmental

Temperature
Operating: -0°C to 50°C
Storage: -40°C to +70°C
Humidity: 95% RH, non condensing at 50°C
Shock: 10 drops 5 ft. to concrete @ room temperature
ESD: Functional after 15KV discharge
Agency: FCC Class B, CE



Complies with EMC 89/336/EEC and LVD 73/23/EEC

Worldwide Offices

Offices Serving North America

Skaneateles Falls, NY
Tel: (315) 685-8945
Fax: (315) 685-3172
Charlotte, NC
Tel: (704) 537-1444
Fax: (704) 532-4191

Offices Serving Europe, Middle East, and Africa

Europe
Tel: Int +31 (0) 40 24 24 486
Fax: Int +31 (0) 40 24 25 672
United Kingdom
Tel: Int +44 (0) 1 925 240055
Fax: Int +44 (0) 1 925 631280
France
Tel: Int +33 (0) 1 461 04111
Fax: Int +33 (0) 1 461 04120

Germany

Tel: Int +49 (0) 7 477 151377
Fax: Int +49 (0) 7 477 151378

Offices Serving Asia and the Pacific Rim

Hong Kong
Tel: Int +852 2511 3050/2511 3132
Fax: Int +852 2511 3557

Japan

Tel: Int +813 52127392
Fax: Int +813 32617372

Offices Serving Latin America

Naples, Florida
Tel: (941) 263-7600
Fax: (941) 263-9689