

Standard Features

External Features



1 Industrial Metal Cabinet

- Rugged corrosion resistant steel enclosure
- Easy to clean surface
- Anti-corrosive, for harsh environments

2 240 x 320 Graphics LCD

- Detailed on-screen messages
- Easier to read
- Non-Latin fonts display
- Customizable with reseller information and end-user logos
- Enhanced Graphics

3 Operator Control Panel

- Sealed for protection from harsh environments
- Simplified User and advanced menu selection
- Navigational and multi-function "soft" keys

4 SDIO & USB Host Ports

- *SDIO Card Slot*
Easily add or transport graphics, fonts, and label formats to your printer.
- *USB Slots*
Two USB slots allows for any USB attachments such as keyboards or memory thumbdrives.

5 Large Side Window

- Continuously monitor media & ribbon supply
- View internal rewind capacity
- Minimize down-time with anticipated media replacement

H-Class

Internal Features



1 IntelliSEAQ™ Printhead

- Advanced diagnostics for maximizing printhead life.
- Precision printhead settings for specific environments.
- Accurately understands usage of the printhead.

4 Split Label Supply Hub

- Die-Cast construction
- Split design allows lower torque on narrow media.
- Supports up to 8" (203mm) O.D. roll
- Hub designs to support 38mm and 76mm cores

2 Dual Platen Rollers

- Improves hard to peel labels when used with the Peel and Present Option.
- Overdriven platen roller improves peel and rewind performance.

5 Fan-Fold Media Slots

Flexible to support rolled or fan folded media behind or below printer.

3 Die-Cast Aluminum Frame

Aluminum construction withstands the harshest environments.

Connectivity Features



1 Parallel Port

- 36 Pin Centronics Connector
- IEEE 1284 Bi-directional support

2 Ethernet Port

- 10/100 BaseT Ethernet Connection
- DHCP Support
- Internal Web Pages for printer control
- SNMP Network Support

3 USB Port (Rear Panel)

- USB 1.1 and 2.0 compatible
- Plug N' Play Ready

4 Serial Port

- 9-Pin Serial Connector
- Configurable for RS-232, 422, and 485
- Supports Baud Speeds up to 115Kbps

5 Power Connection

- Auto-ranging Power Supply, supports voltage ranges from 90 to 132 and 180 to 264 VAC @ 47 - 63 Hz.

6 USB Port (Front Panel)

- 2 USB Ports
- Supports keyboards, scales, flash based thumbdrives, and other peripheral devices